




COMMERCIAL ENTRANCE DETAIL



Commercial Drive Notes:


- Overland Park Municipal Code (OPMC) and Overland Park Design and Construction Standards Manual (OPDCSM) are incorporated, except as otherwise noted.
- 2. KCMMB4K Concrete shall be used throughout.
- 3. Concrete pavement shall be jointed with Type A joints. No jointed slab shall exceed 12' x 12'.
- 4. Detectable warning surfaces are not required at non-signalized
- 5. ADA compliance will be measured at points labeled Elev.
- Sidewalk Ramp shall be lengthened to provide ADA compliant slope, but need not exceed 15'.
- Top of curb elevations shall be shown at quarter points and curb returns.
- Any additional steel reinforcement shall be approved by the City Engineer.
- 11. See Curb Replacement Detail for additional requirements.






Type A (Contraction)

Type B (Isolation)





Type C (Construction)

Type D (Expansion)

JOINT DETAILS Not to Scale

Year 2018 Edition

REVISIONS:	OVERLAND PARK	
Jan. 2005 ADA Compliance;	K A N S A S	
Jan. 2009 Joint Locations; Miscellaneous;		
Jan. 2017 Updated ADA Compliance;	ABOVE AND BEYOND, BY DESIGN.	
	DEPARTMENT OF PUBLIC WORKS	
RELATED ORDINANCES:	STANDARD DETAILS	
OPMC Title 13		
	COMMEDIAL ENTRANCE DETAIL	
	COMMERCIAL ENTRANCE DETAIL	
	DATE: 08/10/98 SHEET: 17	

DRAWING NAME: K:\Details_Specs\Detail_Drawings\details_english\revision_!8\drive-c.dwg WEB SITE ADDRESS: http://www.opkansas.org/Doing-Business/Construction-Details